




KOTWY FUNDAMENTOWE



Zažehlené stoly křesťovské špičkové kůže indonézijské									
№	PROJEKTOV	DLOUHOS [mm]	ŠÍŘKA [mm]	HMOTA [kg/m ²]	TLAKA [atm]	HMOTA [kg/m ²]	TLAKA [atm]	ŠÍŘKA [mm]	HMOTA [kg/m ²]
			STYL						
1	E 200	945	18,4	17,75	48	832,9	923,65		
2	E 200	945	18,4	0,97	48	478,69	535,62		
3	E 3045	200	23,5	0,57	48	371,3	525,65		
4	E 1	60,20	20	12,58	2,59	124,9	525,62		
SUMA [kg]					48	1462,31			
DOPLETKY NA SPONRY [kg]						26,66			
NOVA CELKOVÁ [kg]						1508,99			

NA WSZYSTKICH KOTWACH WYKONANO GWINT M45 NA ODCINKU 120 mm

Wymiary prętów podano w obrysie zewnętrznym

wodoszczelny
PODBETON: C 12/15
STAL: A-IIIIN (#) BST 500S

Otulina od wewnątrz 40 mm
Otulina od zewnątrz 50 mm
Długości zakładów:
—#25—1000 mm

Rysunki K-2, K3, K4, K5 rozpatrywać łącznie

[illegible]